

iPad Wall Mount

Assembly Instructions



iPad Wall Mount

1




Carefully remove iPad components from carton and remove 2x security screws from side of wall mount.

N.B. Your iPad enclosure and VESA plate have been pre-assembled in landscape orientation. However, if you require the iPad in portrait, please remove the VESA plate, rotate through 90° ensuring arrow points towards top of enclosure, and re-attach.

2

Position back plate of wall mount in desired display location and mark hole centres.



For brick/concrete walls, use 8mm masonry bit to drill 4x holes. Insert 4x rawl plugs and secure back plate of mount using screws and washers supplied.



For wood/stud walls, use 4mm wood bit to drill 2x holes. Secure back plate of mount using 2x screws and washers supplied.

3



Unlock the iPad enclosure by inserting key into security lock and rotate 'QUARTER TURN ONLY' clockwise or counter-clockwise through 90 degrees which releases the locking pin. Return key back to original position to remove. Lift fascia out of enclosure and place iPad inside, gently pressing all four corners down into mouldings to hold. Replace fascia and depress lock button to secure enclosure.

iPad Wall Mount

4



Position assembled iPad enclosure and VESA plate over wall mount and lower until both locating pins rest in bracket channels.

5



Adjust tilt to desired angle and re-insert both security screws to secure.